

### Manufacturers' Representatives

☐ George Walker george@beltlink.com (424)410-9119

Southern California, Arizona, and New Mexico

Mike Carroll mike@beltlink.com (805)312-5947

Northern California, Nevada, Utah, and Colorado

 $\square$  Brad Westrick brad@beltlink.com (503)544-6035

Pacific Northwest and British Columbia

### **Conveyor Motorized Pulleys**

- ☐ Food Processing ☐ Packing Sheds ☐ Bulk Handling
- ☐ Logistics ☐ Security Scanning ☐ Distribution Centers

## **USA Fabrication / Short Lead Times**North Carolina factory, German engineering

#### **IP69K Sealing System / Stainless Steel**

**NSF Certified** meets NSF/ANSI/3-A 14159-3 hygiene requirements for meat and poultry conveyors from 80mm to 165mm diameter MPs.

# **Custom Profile, Keyed, and Lagged Shells**Shells with rubber lagging, knurling, key, sleeves, v-guide grooves, machined positive drive profiles.















Wilmington, North Carolina USA



| <b>Motorized Pulley Product Range</b> |        |             |                 |
|---------------------------------------|--------|-------------|-----------------|
| Model                                 | Dia.   | HP          | FPM             |
| <mark>80</mark>                       | 3.21"  | 0.05 = 0.21 | <b>26 - 220</b> |
| 113                                   | 4.47"  | 0.05 - 0.75 | 12 - 384        |
| 138                                   | 5.45"  | 0.13 - 1.33 | 10 - 480        |
| 165                                   | 6.50"  | 0.15 - 3    | 12 - 768        |
| 220                                   | 8.50"  | 0.5 - 7.5   | 30 - 600        |
| 320                                   | 12.64" | 1 - 15      | 24 - 600        |
| 400                                   | 15.75" | 3 - 20      | 38 - 760        |
| 501                                   | 19.72" | 3 - 40      | 48 - 760        |
| 630                                   | 24.80" | 7.5 - 75    | 150-960         |
| 800                                   | 31.50" | 30 - 180    | 240-1064        |
| 1000                                  | 40.16" | 220 - 330   | 600-1320        |